



FT 1165


Avery Dennison FT 1165 is a single liner transfer tape of Flame Tough™ Acrylic recommended for flame retardant requirements within EV battery packs and similar applications.

FEATURES

- Flame retardance
- High tack
- Heavy liner

BENEFITS

- Enables composites to pass UL 94 and other flammability requirements
- Bonds well to low surface energy substrates and foams
- Easier processing for lamination and die cutting



CONSTRUCTION:

Liner:

83# White Kraft

Adhesive:

Flame Tough™ Acrylic

FT 1165

Adhesive Properties:		Typical Values		
Thickness	ASTM D3652	US Mils	MM's	Micron's (µm)
Liner		4.6	0.12	117
Adhesive		2.2	0.06	56
Total Caliper without Liner:		2.2	0.06	56
Total Caliper:		6.8	0.17	173

Peel Adhesion		ASTM D3330		
180° 12 in (300 mm) min @ Room Temp				
Substrate		Lbf / in	N / Meter	
SS	72 HR DWELL	3.5	616	
ABS	72 HR DWELL	2.8	493	
PP	72 HR DWELL	2.6	458	

Loop Tack		ASTM D6195		
180° 32 in (508 mm) / min @ Room Temp				
Substrate		Lbf / in	N / Meter	
SS	INITIAL	2.4	423	

Static Shear		ASTM D3654		
180° 1" sq (6.5 cm ²) 1000 g @ Room Temp				
Substrate		Min to Fail		
SS	24 HR DWELL	> 10,000		

TEMPERATURES	° F	° C
Minimum Service Temperature	50° F	10° C
Maximum Service Temperature	350° F	175° C

THE LISTED VALUES ARE TYPICAL AND NOT INTENDED TO SERVE AS PRODUCT SPECIFICATIONS

APPLICATION TECHNIQUES

- It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied be clean, dry, and free of grease or oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (film / rigid) surface achieves different performance

STORAGE / SHELF LIFE

- One year when stored at 64-72°F (18-22°C) / 30-70% relative humidity, out of direct sunlight and in original packaging.

Please refer to Tapes.AveryDennison.com for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2021 Avery Dennison® Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison® Corporation. All other Avery Dennison® brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison® Corporation.



Performance
Tapes

Asia Pacific
Kunshan, China,
NO. 618 Nanhe Road
Kunshan Economic &
Technological Zone
China, 215335
+86 512 57155001
Fax: +86 512 57155059

Europe
Tieblokkenlaan 1
B-2300 Turnhout
Belgium
+32 (0)14 40 48 11
Fax: +32 (0)14 40 48 55

North America
250 Chester Street
Painesville, Ohio
44077 USA
+1 866-462-8379
Fax: +1 888-358-4469